

ТЕХНИЧЕСКА СПЕСИФИКАЦИЯ

<i>Measure</i>	<i>Diametric Tolerance 3/5 mm</i>	<i>Perimeter</i>	<i>Width Section</i>	<i>I.C. / I.V.</i>	<i>Thick.</i>	<i>Obs.</i>
F / VOYAGER						
195/65 R 15	675 mm	2.120 mm	160 mm	100 H	8.8 mm	
195 R 15	675 mm	2.120 mm	160 mm	100 H	8.8 mm	
235/75 R 15	740 mm	2.323 mm	184 mm	105/104 S	8.8 mm	
30/9.5 R 15	740 mm	2.323 mm	184 mm	105/104 S	8.8 mm	
205/70 R 15	675 mm	2.120 mm	160 mm	96 H	8.8 mm	
255/70 R 15	740 mm	2.323 mm	184 mm	110 H	8.8 mm	
235/70 R 16	740 mm	3.223 mm	184 mm	106/105 H	8.8 mm	
245/70 R 16	751 mm	2.358 mm	184 mm	113/111 H	8.8 mm	
265/70 R 16	783 mm	2.460 mm	209 mm	117/115 H	8.8 mm	
215/65 R 16	699 mm	2.194 mm	176 mm	98 H	8.8 mm	
235/65 R 17	745 mm	2.339 mm	184 mm	108/104 H	8.8 mm	
245/65 R 17	751 mm	2.358 mm	184 mm	113/111 H	8.8 mm	
255/65 R 17	783 mm	2.460 mm	209 mm	98 H	8.8 mm	
265/65 R 17	783 mm	2.460 mm	209 mm	117/115 H	8.8 mm	
F / POWER						
31/10.5 R 15	774 mm	2.430 mm	220 mm	119/112 Q	15 mm	
265/70 R 15	774 mm	2.430 mm	220 mm	119/112 Q	15 mm	
215/85 R 16	785 mm	2.364 mm	175 mm	112/115 Q	13 mm	
235/85 R 16	815 mm	2.559 mm	185 mm	120/116 Q	13 mm	
265/75 R 16	816 mm	2.562 mm	220 mm	116/112 S	15 mm	
285/75 R 16	846 mm	2.656 mm	254 mm	119/122 Q	15 mm	
265/70R 16	816 mm	2.562 mm	220 mm	117 S	15 mm	
305/70 R 16	846 mm	2.656 mm	254 mm	119/120 Q	15 mm	
35/10.5 R 15	846 mm	2.656 mm	254 mm	124 Q	15 mm	
FRONTEIRA - 50% ROAD / 50% OFFROAD						
195/80 R 15	707 mm	2.220 mm	160 mm	100 Q	13 mm	1
195 R 15	707 mm	2.220 mm	160 mm	100 Q	13 mm	1
215/80 R 15	738 mm	2.317 mm	172 mm	100 Q	13 mm	
215 R 15	738 mm	2.317 mm	172 mm	100 Q	13 mm	
205/75 R 15	707 mm	2.220 mm	160 mm	95 Q	13 mm	1
215/75 R 15	738 mm	2.317 mm	172 mm	100 Q	13 mm	
225/75 R 15	738 mm	2.317 mm	172 mm	102 Q	13 mm	
235/75 R 15	751 mm	2.358 mm	190 mm	105 S	13 mm	
30/9.5 R 15	751 mm	2.358 mm	190 mm	105 S	13 mm	
205/70 R 15	707 mm	2.220 mm	160 mm	95 Q	13 mm	1
265/70 R 15	782 mm	2.455 mm	220 mm	106 S	13 mm	1
265/70 R 15	770 mm	2.418 mm	210 mm	106 S	13 mm	2
31/10.5 R 15	782 mm	2.455 mm	220 mm	106 S	13 mm	1
31/10.5 R 15	770 mm	2.418 mm	210 mm	106 S	13 mm	2

Measure	Diametric Tolerance 3/5 mm	Perimeter	Width Section	I.C. / I.V.	Thick.	Obs.
FRONTEIRA - 50% ROAD / 50% OFFROAD						
175 R 16	703 mm	2.209 mm	163 mm	99 Q	13 mm	
185/75 R 16 - C	703 mm	2.209 mm	163 mm	99 Q	13 mm	
205/80 R 16	750 mm	2.355 mm	160 mm	110 S	13 mm	1
205 R 16	750 mm	2.355 mm	160 mm	110 S	13 mm	1
215/85 R 16	809 mm	2.540 mm	160 mm	108 S	13 mm	
225/70 R 16	751 mm	2.358 mm	192 mm	104 S	11 mm	
235/85 R 16	815 mm	2.560 mm	190 mm	120 S	13 mm	
265/75 R 16	793 mm	2.490 mm	215 mm	116 S	13 mm	
245/75 R 16	768 mm	2.411 mm	210 mm	111 S	13 mm	
235/70 R 16	751 mm	2.358 mm	190 mm	105 S	13 mm	
245/70 R 16	768 mm	2.411 mm	210 mm	113 S	13 mm	
255/70 R 16	793 mm	2.490 mm	215 mm	117 S	13 mm	
265/70 R 16	793 mm	2.490 mm	215 mm	117 S	13 mm	
235/60 R 16	706 mm	2.216 mm	212 mm	104 S	13 mm	
600 R 16	703 mm	2.209 mm	163 mm	99 Q	13 mm	
750 R 16	809 mm	2.540 mm	160 mm	108 S	13 mm	1
235/65 R 17	749 mm	2.350 mm	200 mm	104 S	13 mm	
245/65 R 17	768 mm	2.490 mm	200 mm	108/104 S	13 mm	
255/65 R 17	793 mm	2.490 mm	215 mm	117 S	13 mm	
265/65 R 17	793 mm	2.490 mm	215 mm	117 S	13 mm	
Obs. - the numbering 1-2-3 is recorded in the molds						
FRONTEIRA 2 - 50% ROAD / 50% OFFROAD						
195/80 R 15	685 mm	2.150 mm	170 mm	100 Q	13 mm	2
195 R 15	685 mm	2.150 mm	170 mm	100 Q	13 mm	2
205/75 R 15	685 mm	2.150 mm	170 mm	100 Q	13 mm	2
205/70 R 15	675 mm	2.150 mm	170 mm	96 Q	13 mm	2
255/70 R 15	749 mm	2.351 mm	200 mm	110 S	13 mm	2
205/80 R 16	750 mm	2.355 mm	170 mm	110 S	13 mm	2
205 R 16	750 mm	2.355 mm	170 mm	110 S	13 mm	2
F / MUD - 20% ROAD / 80% OFF ROAD						
195 R 15	691 mm	2.171 mm	180 mm	100 Q	15 mm	
195/80 R 15	691 mm	2.171 mm	180 mm	100 Q	15 mm	
215 R 15	733 mm	2.301 mm	190 mm	102/100 Q	15 mm	
215/80 R 15	733 mm	2.301 mm	190 mm	102/100 Q	15 mm	
205/75 R 15	691 mm	2.171 mm	180 mm	100 Q	15 mm	
215/75 R 15	733 mm	2.301 mm	190 mm	100 Q	15 mm	
225/75 R 15	739 mm	2.324 mm	206 mm	104 Q	15 mm	
235/75 R 15	739 mm	2.324 mm	206 mm	105/104 Q	15 mm	
30/9.5 R 15	739 mm	2.324 mm	206 mm	105/104 Q	15 mm	
205/70 R 15	691 mm	2.171 mm	180 mm	100 Q	15 mm	
265/70 R 15	789 mm	2.480 mm	220 mm	109 Q	15 mm	

Measure	Diametric Tolerance 3/5 mm	Perimeter	Width Section	I.C. / I.V.	Thick.	Obs.
F / MUD - 20% ROAD / 80% OFF ROAD						
31x10.5 R 15	789 mm	2.480 mm	220 mm	109 Q	15 mm	
35/10.5 R 15	846 mm	2.656 mm	254 mm	124 Q	15 mm	
235/85 R 16	818 mm	2.571 mm	205 mm	120 Q	15 mm	
205 R 16	750 mm	2.360 mm	190 mm	110 Q	15 mm	
205/80 R 16	750 mm	2.360 mm	190 mm	110 Q	15 mm	
215/80 R 16	770 mm	2.417 mm	190 mm	107 Q	13 mm	
225/75 R 16	760 mm	2.385 mm	212 mm	105 Q	15 mm	
265/75 R 16	798 mm	2.506 mm	220 mm	116/112 S	15 mm	
235/70 R 16	760 mm	2.385 mm	212 mm	105 Q	15 mm	
245/70 R 16	760 mm	2.385 mm	212 mm	107/105 Q	15 mm	
255/70 R 16	798 mm	2.506 mm	220 mm	117 S	15 mm	
265/70 R 16	798 mm	2.506 mm	220 mm	117 S	15 mm	
235/60 R 16	709 mm	2.226 mm	212 mm	105 Q	15 mm	
750 R 16	818 mm	2.571 mm	205 mm	120 Q	15 mm	
235/65 R 17	760 mm	2.385 mm	212 mm	108/104 S	15 mm	
255/65 R 17	798 mm	2.506 mm	220 mm	117 S	15 mm	
265/65 R 17	798 mm	2.506 mm	220 mm	110/112 S	15 mm	
EXTREME - 20% ROAD / 80% OFF ROAD						
185 R 14 - C	663 mm	2.081 mm	155 mm	102 Q	16.5 mm	1
185 R 14 - C	676 mm	2.125 mm	180 mm	106/104 Q	16.5 mm	2
185 R 14 - C	666 mm	2.091 mm	170 mm	106/104 Q	16.5 mm	2
195 R 14	676 mm	2.125 mm	180 mm	100 Q	16.5 mm	
195/75 R 14	676 mm	2.125 mm	180 mm	100 Q	16.5 mm	
195 R 15	676 mm	2.125 mm	180 mm	100 Q	16.5 mm	
195/70 R 15 - C	676 mm	2.125 mm	180 mm	104/102 Q	16.5 mm	
205/80 R 15 - C	756 mm	2.380 mm	190 mm	110 Q	16.5 mm	1
215/80 R 15	747 mm	2.350 mm	200 mm	105/104 Q	16.5 mm	2
215 R 15	747 mm	2.350 mm	200 mm	105/104 Q	16.5 mm	2
205/75 R 15	676 mm	2.125 mm	180 mm	100 Q	16.5 mm	
205/70 R 15	676 mm	2.125 mm	180 mm	100 Q	16.5 mm	
215/75 R 15	730 mm	2.295 mm	200 mm	100 Q	16.5 mm	
225/75 R 15	747 mm	2.350 mm	200 mm	105/104 Q	16.5 mm	
235/75 R 15	756 mm	2.375 mm	210 mm	105/104 Q	16.5 mm	1
30/9.50 R 15	756 mm	2.375 mm	210 mm	105/104 Q	16.5 mm	1
265/70 R 15	774 mm	2.430 mm	240 mm	112/109 Q	16.5 mm	
31/10.5 R 15	774 mm	2.430 mm	240 mm	112/109 Q	16.5 mm	
750 R 16	820 mm	2.575 mm	210 mm	120 Q	16.5 mm	2
175 R 16	698 mm	2.192 mm	155 mm	90 Q	16.5 mm	1
175/75 R 16 - C	688 mm	2.155 mm	155 mm	101/99 Q	16.5 mm	1
185/75 R 16 - C	698 mm	2.192 mm	155 mm	90 Q	16.5 mm	1
175 R 16	686 mm	2.155 mm	155 mm	90 Q	16.5 mm	2
600 R 16	698 mm	2.192 mm	155 mm	90 Q	16.5 mm	

Measure	Diametric Tolerance 3/5 mm	Perimeter	Width Section	I.C. / I.V.	Thick.	Obs.
EXTREME - 20% ROAD / 80% OFF ROAD						
205/80 R 16	756 mm	2.380 mm	190 mm	110 Q	16.5 mm	1
205 R 16	756 mm	2.380 mm	190 mm	110 Q	16.5 mm	1
205 R 16	747 mm	2.350 mm	200 mm	110 Q	16.5 mm	2
205 R 16	730 mm	2.295 mm	200 mm	110 Q	16.5 mm	3
215/75 R 16 - C	747 mm	2.350 mm	200 mm	110 Q	16.5 mm	2
235/85 R 16	826 mm	2.600 mm	210 mm	120 Q	16.5 mm	1
235/85 R 16	820 mm	2.575 mm	210 mm	120 Q	16.5 mm	2
205/75 R 16	730 mm	2.295 mm	200 mm	110 Q	16.5 mm	3
235/70 R 16	756 mm	2.375 mm	210 mm	107/105 Q	16.5 mm	
245/70 R 16	756 mm	2.375 mm	210 mm	107/105 Q	16.5 mm	
255/70 R 16	803 mm	2.520 mm	240 mm	117 Q	16.5 mm	
265/70 R 16	803 mm	2.520 mm	240 mm	117 Q	16.5 mm	
225/65 R 16 - C	730 mm	2.295 mm	200 mm	110 Q	16.5 mm	3
215/65 R 16	730 mm	2.295 mm	200 mm	110 Q	16.5 mm	
Obs. - the numbering 1-2-3 is recorded in the molds						
EXTREME EVOLUTION - 20% ROAD / 80% OFF ROAD						
195/80 R 15	716 mm	2.250 mm	180 mm	100 Q	16.5 mm	
195 R 15	716 mm	2.250 mm	180 mm	100 Q	16.5 mm	
205/75 R 15	716 mm	2.250 mm	180 mm	100 Q	16.5 mm	
235/75 R 15	760 mm	2.385 mm	217 mm	105 Q	16.5 mm	
30/9.50 R 15	760 mm	2.385 mm	217 mm	105 Q	16.5 mm	
205/70 R 15	716 mm	2.250 mm	180 mm	100 Q	16.5 mm	
255/70 R 15	760 mm	2.385 mm	217 mm	108/104 S	16.5 mm	
265/70 R 15	773 mm	2.425 mm	240 mm	112/109 Q	16.5 mm	
31/10.5 R 15	773 mm	2.430 mm	240 mm	112/109 Q	16.5 mm	
225/75 R 16	760 mm	2.385 mm	217 mm	104 T	16.5 mm	
235/70 R 16	760 mm	2.385 mm	217 mm	107/105 Q	16.5 mm	
245/70 R 16	760 mm	2.385 mm	217 mm	107/105 Q	16.5 mm	
750 R 16	820 mm	2.573 mm	210 mm	120 Q	16.5 mm	
235/85 R 16	822 mm	2.570 mm	210 mm	120 Q	16.5 mm	
TRIAL - 20% ROAD / 80% OFF ROAD						
33/12.5 R 15	834 mm	2.62 mm	260 mm	108 Q	15 mm	
TRIAL ADE - 20% ROAD / 80% OFF ROAD						
31/10.5 R 15	775 mm	2.430 mm	220 mm	109 Q	18 mm	
265/70 R 15	775 mm	2.430 mm	220 mm	109 Q	18 mm	
900 R 15	925 mm	2.890 mm	205 mm	124 Q	18 mm	
265/75 R 16	800 mm	2.510 mm	215 mm	112 Q	18 mm	
265/70 R 16	800 mm	2.510 mm	215 mm	112 Q	18 mm	
31/10.5 R 16	825 mm	2.890 mm	205 mm	124 Q	18 mm	

Measure	Diametric Tolerance 3/5 mm	Perimeter	Width Section	I.C. / I.V.	Thick.	Obs.
MAXIMA - 20% ROAD / 80% OFF ROAD						
700 R 16	792 mm	2.486 mm	145 mm	117/116 L	15 mm	
700 x 16	792 mm	2.486 mm	145 mm	117/116 L	15 mm	
750 R 16	814 mm	2.556 mm	160 mm	112/110 L	15 mm	
750 x 16	814 mm	2.556 mm	160 mm	112/110 L	15 mm	
MAXIMA 2 - 20% ROAD / 80% OFF ROAD						
700 R 15	760 mm	2.380 mm	145 mm	114/112 L	14 mm	
700 x 15	760 mm	2.380 mm	145 mm	114/112 L	14 mm	
650 R 16	760 mm	2.380 mm	145 mm	114/112 L	14 mm	
650 x 16	760 mm	2.380 mm	145 mm	114/112 L	14 mm	
T & C - TOWN & COUNTRY - 20% ROAD / 80% OFF ROAD						
750 R 16	807 mm	2.533 mm	153 mm	112/110 Q	13 mm	
750 R 16	807 mm	2.533 mm	153 mm	112/110 Q	13 mm	
F / CROSS - 20% ROAD / 80% OFF ROAD						
235/85 R 16	843 mm	2.650 mm	223 mm	120 N	25 mm	
SIROCCO - 20% ROAD / 80% OFF ROAD						
195/80 R 15	720 mm	2.260 mm	195 mm	100 Q	19 mm	
195 R 15	720 mm	2.260 mm	195 mm	100 Q	19 mm	
205/70 R 15	720 mm	2.260 mm	197 mm	95 Q	19 mm	
215/80 R 15	731 mm	2.295 mm	208 mm	100 Q	19 mm	
215 R 15	731 mm	2.295 mm	208 mm	100 Q	19 mm	
205/75 R 15	720 mm	2.260 mm	197 mm	95 Q	19 mm	
215/75 R 15	731 mm	2.295 mm	208 mm	100 Q	19 mm	
225/75 R 15	732 mm	2.299 mm	208 mm	100 Q	19 mm	
235/75 R 15	762 mm	2.392 mm	230 mm	104 Q	19 mm	
30/9.50 R 15	762 mm	2.392 mm	230 mm	104 Q	19 mm	
255/70 R 15	762 mm	2.392 mm	230 mm	105 Q	19 mm	
265/70 R 15	801 mm	2.515 mm	243 mm	109 Q	19 mm	
31/10.5 R 15	801 mm	2.515 mm	243 mm	109 Q	19 mm	
195 R 16	720 mm	2.260 mm	197 mm	104 Q	19 mm	
205/80 R 16	750 mm	2.355 mm	208 mm	104 Q	19 mm	
205 R 16	750 mm	2.355 mm	208 mm	104 Q	19 mm	
235/85 R 16	838 mm	2.630 mm	232 mm	120 Q	19 mm	
285/75 R 16	756 mm	2.687 mm	283 mm	116 Q	19 mm	
235/70 R 16	762 mm	2.392 mm	230 mm	105 Q	19 mm	
245/70 R 16	762 mm	2.392 mm	230 mm	105 Q	19 mm	
305/70 R 16	856 mm	2.687 mm	283 mm	116/115 Q	19 mm	
750 R 16	838 mm	2.630 mm	232 mm	120 Q	19 mm	
900 R 16	932 mm	2.930 mm	245 mm	124 Q	19 mm	1
900 R 16	856 mm	2.687 mm	283 mm	116 Q	19 mm	2

Measure	Diametric Tolerance 3/5 mm	Perimeter	Width Section	I.C. / I.V.	Thick.	Obs.
SIROCCO - 20% ROAD / 80% OFF ROAD						
35/10.5 R 16	932 mm	2.930 mm	245 mm	124 Q	19 mm	1
35/10.5 R 16	856 mm	2.687 mm	283 mm	116 Q	19 mm	2
SIROCCO 2 - 20% ROAD / 80% OFF ROAD						
235/85 R 16	825 mm	2.590 mm	255 mm	120 Q	19 mm	
265/75 R 16	825 mm	2.590 mm	255 mm	120 Q	19 mm	
265/70 R 16	825 mm	2.590 mm	255 mm	120 Q	19 mm	
275/70 R 16	825 mm	2.590 mm	255 mm	120 Q	19 mm	
FPC 4 x 4 - 80% ROAD / 20% OFF ROAD						
195 R 15	700 mm	2.198 mm	160 mm	95 Q	10 mm	
215/80 R 15	734 mm	2.305 mm	170 mm	102 S	10 mm	
215 R 15	734 mm	2.305 mm	170 mm	102 S	10 mm	
205/70 R 15	700 mm	2.198 mm	160 mm	95 Q	10 mm	
31/10.5 R 15	777 mm	2.440 mm	205 mm	109 Q	10 mm	
265/70 R 15	777 mm	2.440 mm	205 mm	109 Q	10 mm	
205/80 R 16	741 mm	2.327 mm	170 mm	104 Q	10 mm	
205/75 R 16	734 mm	2.305 mm	170 mm	110/108 Q	10 mm	
WRANGLER - 80% ROAD / 20% OFF ROAD						
235/75 R 15	739 mm	2.320 mm	185 mm	105 Q	10 mm	
M + S 244 - 80% ROAD / 20% OFF ROAD						
205 R 16	745 mm	2.340 mm	160 mm	110 Q	11 mm	
PARTNER						
195/80 R 15	716 mm	2.250 mm	180 mm	100 Q	16.5 mm	1
195 R 15	716 mm	2.250 mm	180 mm	100 Q	16.5 mm	1
195 R 15	674 mm	2.116 mm	165 mm	100 Q	16.5 mm	2
195/75 R 15	674 mm	2.116 mm	165 mm	100 Q	16.5 mm	
205/75 R 15	674 mm	2.116 mm	165 mm	97 Q	16.5 mm	
205/70 R 15	674 mm	2.116 mm	165 mm	97 Q	16.5 mm	
205/90 R 16	795 mm	2.249 mm	165 mm	110 Q	10.5 mm	
215/80 R 16	795 mm	2.249 mm	165 mm	110 Q	10.5 mm	
215/85 R 16	795 mm	2.249 mm	165 mm	110 Q	16.5 mm	
175 R 16	710 mm	2.230 mm	175 mm	90 Q	16.5 mm	
195 R 16	716 mm	2.250 mm	180 mm	102 Q	16.5 mm	
700 R 16	795 mm	2.496 mm	165 mm	108 Q	16.5 mm	
750 R 16	795 mm	2.496 mm	165 mm	120 Q	16.5 mm	
185/75 R 16	716 mm	2.250 mm	180 mm	90 Q	16.5 mm	
185/75 R 16 - C	710 mm	2.230 mm	175 mm	90 Q	16.5 mm	
215/70 R 16	716 mm	2.250 mm	180 mm	102 Q	16.5 mm	

Measure	Diametric Tolerance 3/5 mm	Perimeter	Width Section	I.C. / I.V.	Thick.	Obs.
F - GUIDE						
205/90 R 16	786 mm	2.470 mm	165 mm	-	10.5 mm	
215/80 R 16	786 mm	2.470 mm	165 mm	-	10.5 mm	
235/80 R 16	809 mm	2.540 mm	180 mm	-	10.5 mm	
205/85 R 16	746 mm	2.342 mm	165 mm	-	10.5 mm	
FA2						
205/90 R 16	786 mm	2.470 mm	160 mm	-	10 mm	
215/80 R 16	786 mm	2.470 mm	160 mm	-	10 mm	
205/90 R 16	786 mm	2.470 mm	165 mm	-	10.5 mm	
215/80 R 16	786 mm	2.470 mm	165 mm	-	10.5 mm	
MAXI - GRIP						
195 R 15	717 mm	2.251 mm	180 mm	100 Q	16 mm	
195/80 R 15	717 mm	2.251 mm	180 mm	100 Q	16 mm	
205/70 R 15	717 mm	2.251 mm	180 mm	95 Q	16 mm	
195 R 16	717 mm	2.251 mm	180 mm	100 Q	16 mm	
235/85 R 16	825 mm	2.590 mm	212 mm	120 Q	16 mm	
F / TERRAIN						
245/80R 16	809 mm	2.540 mm	195 mm	-	10.5 mm	
AUTOCROSS F 4						
155/70 R 13	564 mm	1.775 mm	145 mm	75 T	10 mm	
175/70 R 13	594 mm	1.870 mm	155 mm	82 T	10 mm	
165/70 R 14	605 mm	1.900 mm	150 mm	81 T	10 mm	
14/60 - 14 *	605 mm	1.900 mm	150 mm	-	10 mm	
185/60 R 14	594 mm	1.870 mm	165 mm	82 T	10 mm	
20/68 - 15	704 mm	2.210 mm	200 mm	100 T	10 mm	
18/66 - 15	665 mm	2.088 mm	204 mm	100 T	10.5 mm	
205/70 R 15	685 mm	2.150 mm	170 mm	95 T	10.5 mm	
175/65 R 15	625 mm	1.962 mm	155 mm	84 T	10 mm	
185/65 R 15	640 mm	2.009 mm	160 mm	88 T	10.5 mm	
195/65 R 15	647 mm	2.031 mm	180 mm	91 T	10 mm	
215/65 R 15	663 mm	2.081 mm	180 mm	100 T	10 mm	
17/65 - 15	663 mm	2.081 mm	180 mm	100 T	10 mm	
14/62 - 15 *	663 mm	2.081 mm	180 mm	-	10 mm	
195/60 R 15	633 mm	1.990 mm	180 mm	87 T	10 mm	
205/60 R 15	633 mm	1.990 mm	180 mm	91 T	10 mm	
185/55 R 15	584 mm	1.834 mm	185 mm	81 T	10 mm	
195/50 R 15	584 mm	1.834 mm	185 mm	82 T	10 mm	
16/68 - 16	703 mm	2.207 mm	175 mm	107 N	10 mm	
205/50 R 16	633 mm	1.990 mm	180 mm	82 T	10 mm	

* - Measures without I.C. / I.V. - only for competition.

Measure	Diametric Tolerance 3/5 mm	Perimeter	Width Section	I.C. / I.V.	Thick.	Obs.
F / POWER						
205/90 R 16	785 mm	2.364 mm	175 mm		13 mm	
215/85 R 16	785 mm	2.364 mm	175 mm		13 mm	
235/85 R 16	815 mm	2.559 mm	185 mm		13 mm	
F / Kx						
165/70 R 14	612 mm	1.921 mm	140 mm	81 T	15 mm	
14/62 - 14	612 mm	1.921 mm	140 mm	81 T	15 mm	
17/68 - 15	656 mm	2.059 mm	170 mm	91 T	15 mm	
175/65 R 15	633 mm	1.988 mm	150 mm	84 T	15 mm	
185/65 R 15	633 mm	1.988 mm	150 mm	92 R	15 mm	
195/65 R 15	656 mm	2.059 mm	170 mm	95 T	15 mm	
15/63 - 15	633 mm	1.988 mm	150 mm	84 T	15 mm	
F / M 7						
165/70 R 14	602 mm	1.890 mm	146 mm	89 T	10.5 mm	
175/65 R 15	623 mm	1.956 mm	160 mm	84 T	10.5 mm	
195/65 R 15	645 mm	2.025 mm	180 mm	91 T	10.5 mm	
F / OR						
155/80 R 13	588 mm	1.846 mm	150 mm	79 Q	9.5 mm	
165/70 R 13	565 mm	1.774 mm	140 mm	88 R	9.5 mm	
165/70 R 14	580 mm	1.821 mm	150 mm	89 R	10 mm	
175/65 R 14	580 mm	1.821 mm	150 mm	89 R	10 mm	
195/80 R 15	695 mm	2.182 mm	163 mm	96 R	10 mm	
195 R 15	695 mm	2.182 mm	163 mm	96 R	10 mm	
175/65 R 15	625 mm	1.963 mm	155 mm	84 R	11 mm	
205/75 R 15	695 mm	2.182 mm	163 mm	96 R	10 mm	
205/70 R 15	695 mm	2.182 mm	163 mm	96 R	10 mm	
195/70 R 15	660 mm	2.072 mm	163 mm	104/102 Q	10 mm	
185/65 R 15	625 mm	1.963 mm	155 mm	92 R	11 mm	
195/65 R 15	660 mm	2.072 mm	163 mm	95 T	10 mm	
195 R 16	695 mm	2.182 mm	163 mm	104/102 R	10 mm	
205 R 16	710 mm	2.229 mm	175 mm	110 R	10 mm	
195/65 R 16	695 mm	2.182 mm	163 mm	104/102 R	10 mm	
215/65 R 16 - C	695 mm	2.182 mm	163 mm	104/102 R	10 mm	
185/75 R 16	695 mm	2.182 mm	163 mm	104/102 R	10 mm	
195/75 R 16	695 mm	2.182 mm	163 mm	107/105 R	10 mm	
205/75 R 16	710 mm	2.229 mm	175 mm	110/108 R	10 mm	
205/75 R 16	710 mm	2.229 mm	175 mm	110/108 R	10 mm	
215/85 R 16	786 mm	2.470 mm	165 mm	110 N	10.5 mm	
205/80 R 16	710 mm	2.229 mm	175 mm	110 R	10 mm	
215/80 R 16	786 mm	2.470 mm	165 mm	103 N	10.5 mm	
205/75 R 16	710 mm	2.229 mm	175 mm	110/108 R	10 mm	
265/65 R 17	785 mm	2.468 mm	220 mm	110 R	10 mm	

Measure	Diametric Tolerance 3/5 mm	Perimeter	Width Section	I.C. / I.V.	Thick.	Obs.
F / OR - 2						
165/70 R 14 C	602 mm	1.890 mm	147 mm	89 H	10 mm	
16/53 R 13	550 mm	1.712 mm	167 mm	80 H	6 mm	
F / T						
16/53 R 13	550 mm	1.712 mm	167 mm	80 H	6 mm	
185/60 R 13	550 mm	1.712 mm	167 mm	80 H	6 mm	
185/60 R 14	586 mm	1.845 mm	165 mm	82 H	6 mm	
175/60 R 15	583 mm	1.828 mm	180 mm	82 V	6 mm	
18/58 - 15	583 mm	1.828 mm	180 mm	82 V	6 mm	
195/50 R 15	583 mm	1.828 mm	180 mm	82 V	6 mm	
185/55 R 15	583 mm	1.828 mm	180 mm	82 V	6 mm	
215/45 R 17	637 mm	2.000 mm	198 mm	91 H	6 mm	
225/45 R 17	637 mm	2.000 mm	198 mm	91 H	6 mm	
F / N						
155/70 R 13	553 mm	1.736 mm	130 mm	75 T	6.5 mm	
185/60 R 14	582 mm	1.829 mm	165 mm	82 H	6.5 mm	
175/60 R 15	584 mm	1.834 mm	172 mm	81 V	6.5 mm	
18/58 - 15	584 mm	1.834 mm	172 mm	81 V	6.5 mm	
185/55 R 15	584 mm	1.834 mm	172 mm	82 V	6.5 mm	
195/50 R 15	584 mm	1.834 mm	172 mm	82 V	6.5 mm	
205/55 R 16	634 mm	1.990 mm	180 mm	91 V	6.5 mm	
215/45 R 17	636 mm	2.002 mm	200 mm	91 V	6.5 mm	
225/45 R 17	636 mm	2.002 mm	200 mm	91 V	6.5 mm	
ASFALTO RALLY "SLICK"						
195/50 R 15	577.5 mm	1.815 mm	195 mm	82 V	6 mm	
F / EN						
145/70 R 13	554 mm	1.740 mm	118 mm	68 T	7 mm	
155/70 R 13	554 mm	1.740 mm	118 mm	75 T	7 mm	
175/70 R 13	583 mm	1.830 mm	132mm	82 V	7.5 mm	
185/60 R 14	584 mm	1.833 mm	145 mm	82 H	7.5 mm	
185/55 R 15	580 mm	1.821 mm	175 mm	82 V	7.5 mm	
195/50 R 15	504 mm	1.821 mm	175 mm	82 V	7.5 mm	
F / EN DINAMIC						
185/70 R 14	622 mm	1.971 mm	150 mm	88 T	7.5 mm	
175/65 R 14	591 mm	1.856 mm	143 mm	82 H	7.5 mm	
185/65 R 15	628 mm	1.971 mm	150 mm	88 H	7.5 mm	
195/65 R 15	640 mm	2.009 mm	155 mm	95 V	7.5 mm	

Measure	Diametric Tolerance 3/5 mm	Perimeter	Width Section	I.C. / I.V.	Thick.	Obs.
<i>F / S2</i>						
195/55 R 15	580 mm	1.821 mm	175 mm	88 H	7.5 mm	
185/60 R 15	580 mm	1.821 mm	175 mm	88 H	7.5 mm	
195/60 R 15	620 mm	1.946 mm	150 mm	88 T	7.5 mm	
205/55 R 15	620 mm	1.946 mm	150 mm	88 T	7.5 mm	
205/60 R 16	658 mm	2.066 mm	170 mm	82 H	8 mm	
205/55 R 16	638 mm	2.003 mm	169 mm	91 V	7.5 mm	
205/50 R 17	646 mm	2.028 mm	170 mm	89 V	8 mm	
215/45 R 17	635 mm	1.994 mm	200 mm	91 W	8 mm	
225/45 R 17	635 mm	1.994 mm	200 mm	91 W	8 mm	
235/45 R 17	635 mm	1.994 mm	200 mm	91 W	8 mm	
<i>PRESTIGE</i>						
165/70 R 13	569 mm	1.786 mm	125 mm	79 T	8 mm	
<i>HP 10 WINTER / HP ONE</i>						
145/80 R 13	578 mm	1.816 mm	136 mm	79 Q	11.5 mm	
155/80 R 13	588 mm	1.846 mm	132 mm	79 Q	10.5 mm	
175/70 R 13	590 mm	1.853 mm	140mm	82 T	10.5 mm	
175/65 R 14	598 mm	1.880 mm	148 mm	82 T	10.5 mm	
185/65 R 15	635 mm	1.993 mm	150 mm	88 H	10.5 mm	
195/60 R 15	647 mm	2.032 mm	162 mm	95 T	10.5 mm	
205/55 R 16	643 mm	2.020 mm	171 mm	91 H	10.5 mm	
225/45 R 17	643 mm	2.019 mm	190 mm	91 V	9.5 mm	
<i>WINTER M+S</i>						
155/80 R 13	590 mm	1.852 mm	130 mm	85/83 Q	11.5 mm	
165/70 R 13	578 mm	1.816 mm	136 mm	88/86 R	11.5 mm	
175 R 14	647 mm	2.031 mm	150 mm	102/100 Q	11.5 mm	
185 R 14	647 mm	2.031 mm	150 mm	102/100 Q	11.5 mm	
185/75 R 14	647 mm	2.031 mm	150 mm	102/100 Q	11.5 mm	
165/70 R 14	599 mm	1.880 mm	145 mm	90/88 T	11.5 mm	
175/65 R 14	598 mm	1.880 mm	145 mm	90/88 T	11.5 mm	
195/70 R 15	664 mm	2.085 mm	178 mm	104/102 R	12 mm	
225/70 R 15	707 mm	2.210 mm	198 mm	112/110 R	12 mm	
185/75 R 16	708 mm	2.223 mm	150 mm	107/105 R	12 mm	
195/75 R 16	708 mm	2.223 mm	150 mm	107/105 R	12 mm	
<i>HP 3</i>						
235/75 R 15	740 mm	2.324 mm	195 mm	105 S	9.5 mm	
30/9.5 R 15	740 mm	2.324 mm	195 mm	105 S	9.5 mm	
265/75 R 16	784 mm	2.590 mm	255 mm	120L	9.5 mm	
235/70 R 16	740 mm	2.324 mm	195 mm	105 S	9.5 mm	
265/70 R 16	784 mm	2.462 mm	216 mm	112 S	9.5 mm	

Measure	Diametric Tolerance 3/5 mm	Perimeter	Width Section	I.C. / I.V.	Thick.	Obs.
AGIL / 51						
185/75 R 14	658 mm	2.066 mm	145 mm	102/100 N	11 mm	
185 R 14	658 mm	2.066 mm	145 mm	102/100 N	11 mm	
195/75 R 14	658 mm	2.066 mm	145 mm	106/104 N	11 mm	
225/70 R 15	703 mm	2.207 mm	178 mm	112/110 R	11 mm	
195/75 R 16	701 mm	2.201 mm	160 mm	107/105 R	11 mm	
F / CARGO 81						
195/75 R 16	703 mm	2.207 mm	160 mm	107/105 R	11 mm	
205/65 R 16	882 mm	2.141 mm	163 mm	107/105 R	11 mm	